


CLEANOUT SHALL BE PLACED AT RIGHT-OF-WAY OR EDGE OF EASEMENT. DO NOT INSTALL CLEANOUT INSIDE A FENCE.

SECTION VIEW

- NOTES:**
- 1) INSTALLATION TO BE THE SAME AS FOR STANDARD 4 INCH SEWER SERVICE CONNECTION (SHEET 1 OF 3).
 - 2) CONTRACTOR MAY BE REQUIRED TO LAY CONNECTIONS AT 1% (REGARDLESS OF DEPTH) IN ORDER TO SERVE CUSTOMER. IN THIS CASE, 1/8 BEND WILL NOT BE USED.
 - 3) CONNECTIONS TO 15" OUTFALLS AND GREATER MUST BE MADE INTO MANHOLE.

1/16 BEND IF WYE IS USED



IN LINE WYE FITTING OR APPROVED TAPPING SADDLE PROVIDED AT TOP QUARTER OF THE MAIN. IN LINE WYE IS REQUIRED FOR SANITARY SEWER SERVICES INSTALLED WITH NEW CONSTRUCTION WHEN PARCEL AND SERVICE LOCATIONS ARE KNOWN AND IDENTIFIED ON APPROVED PLANS.

EFFECTIVE: 12/10/09

DEEP 4 INCH SANITARY SEWER SERVICE WITH TAP

DETAIL No.
07000.10
SHEET 2 OF 3